TYPICAL BUILD SPECS

FOUNDATION

9' or 10' poured concrete basement walls (per plan) Rockwell fiberglass window wells or timber window wells Sump pit, sump pump, and water powered sump jet back up

FRAMING

2" x 6" exterior wall construction 10' main floor ceiling height and 9' second level 8'8" or 9'8" basement ceiling heights

HVAC

96% AFUE rating Heil variable speed gas furnace and 14 SEER Heil Cooling system Nest thermostat and zoned system

ELECTRICAL

400 AMP service
Ample can lighting and designer fixtures included

PLUMBING

PEX water lines
Water softener rough in
Delta fixtures

INSULATION

Open cell R-21 spray foam on exterior walls

WINDOWS

Homeguard Energy Star Casement or Double hung windows (per plan)

INTERIOR FINISHES

Premium engineered 1/2" hardwoods, luxury plank, upgraded carpets Designer porcelain and marble tiles in bathrooms and at backsplashes Sherwin Williams interior and exterior paints

Upgraded trim packages available

Custom metal stair railings

Custom Amish built kitchen with designer features and pro appliances Built-ins, optional cabinetry and fireplaces per plans

HOME EXTERIOR

Stone skirt (per plan)
James Hardie Fiber cement siding and trim
Owens Corning Duration Dimensional shingle
6" aluminum gutters

LANDSCAPING AND IRRIGATION

Professionally planned landscaping and irrigation system

HOME WARRANTY

2-10 home builders warranty







